




Date	SYM	REVISION RECORD	AUTH	DR.	CK.
02/29/08	A	REDRAWN ADDED "ROHS COMPLIANT"	T.B.	B.S.	
09/10/10	B	ADDED DIM. 6.22 FOR PIN LOCATION	T.B.	B.S.	
06/13/14	C	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	



PCB LAYOUT

SPECIFICATIONS:

HOLDER MATERIAL: SELF EXTINGUISHING THERMOPLASTIC,
BLACK PBT

FLAMMABILITY RATING:UL94V-0, FILE #E41797

CONTACTS: 301 SPRING TEMPER STAINLESS STEEL, NICKEL
PLATED OVERALL

DIELECTRIC STRENGTH: 560 VOLTS/MIL AT 25°C FOR 5 SEC.

TEMPERATURE RANGE: -55°C TO +140°C

RESISTANCE TO SOLVENTS: XYLENE, ETHYL , BUTYL, METHYL,
PROPYL ALCOHOL, ETHYL ACETATE,
HEPTANE, TOLUENE, REFRIGERANT

NOTES:

EYELET STIMPSON STYLE#A1883 0.110" OD x 0.190" FLANGE

FLANGE RECESS Ø0.203" x 0.090" DEEP

ACCEPTS STANDARD 2-56 MACHINE SCREWS

ACCESSORIES: BI-UM-3-4, INSULATOR

ROHS 2 COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal ±.5 (.020)	Scale		Drawn By B.S.
Fractional ± .8 (.030)	Title		Approved By T.B.
Angular ± 3°	Date 6/13/14	Drawing Number BH1/3N-C	